

Respina Lithium R

General-purpose regular load lithium greases



Description

Respina Lithium R greases are general general-purpose greases having mineral base oil, lithium soap thickener and an advanced additive package. They are suitable for a wide range of industrial and automotive applications as general fireproof greases where the operating temperature range is from -20°C to 130°C.

Specification and Approvals:

DIN 51825

Advantages & Benefits

- Long-term lubrication of roller and plain bearings
- Excellent anti-friction properties
- Excellent anti-rust and anti-corrosion properties
- Resistance to water washout for equipment protection

Typical Data

| Property | unit | R 0 | R 1 | R 2 | R 3 | Test method |
|--------------------|---------|---------|---------|---------|---------|-------------|
| NLGI | - | 0 | 1 | 2 | 3 | ASTM D217 |
| Thickener | - | Lithium | Lithium | Lithium | Lithium | - |
| Color | - | brown | brown | brown | brown | Visual |
| Viscosity at 40°C | Cst | 100 | 100 | 100 | 100 | ASTM D445 |
| Viscosity at 100°C | Cst | 11 | 11 | 11 | 11 | ASTM D445 |
| Drop Point | °C | 185 | 190 | 190 | 190 | ASTM D2265 |
| Worked penetration | 1/10 mm | 355-385 | 310-340 | 265-295 | 220-250 | ASTM D217 |

❖ Respina Lithium R greases are formulated and produced in RESPINA LUBRICANTS blending site and presented data is based on standard tests under laboratory conditions and is given as a guide only. These characteristics are typical of current production and acceptable variation may occur.

