



Castrol Aircol SR Range

Synthetic Rotary Compressor Lubricant

Description

The Castrol Aircol™ SR compressor oil range of premium lubricants are designed for use in rotary screw compressors and are based on polyalphaolefin (PAO) fluids.

Application

Aircol SR is suitable for use in oil flooded rotary screw compressors operating under extreme climatic conditions, harsh environments and severe operating conditions where very high air discharge temperatures ($> 100^{\circ}\text{C}$) are experienced. These oils are also suitable for use in compressor units operating at normal operating conditions, with the maximum air discharge temperature $\leq 100^{\circ}\text{C}$, as defined by ISO 6743-3:2003.

For normal operating conditions, these products can be used for extended drain intervals up to 8000 hours.

Aircol SR range is fully compatible with nitrile, silicone, polyurethane and fluropolymer seal materials typically used in compressor units. It is not compatible with butadiene styrene (SBR) or ethylene propylene (EPDM) seals.

Aircol SR is classified as follows:

- DIN 51506 classification - VDL
- ISO 6743/3 - DAG, DAH and DAJ for rotary air compressors

Aircol SR grades meet the requirements of:

- Atlas Copco 8000 hour oil drain interval
- Kaeser

Advantages

- Increased oil service life of typically up to 8000 hours in most systems, depending on the operating environment.
- Very low deposit forming tendency, extends service life of filters and separators.
- Outstanding oxidation stability and antiwear performance providing long lubricant and equipment life.
- Ester-free formulation eliminates the formation of corrosive acids leading to longer equipment life.
- Excellent water separation characteristics allow condensation to readily separate from the oil, minimizing the risk of emulsions which could block the oil separator element.
- PAO based lubricant means good compatibility with seals and mineral oil based lubricants, allowing changeover to Aircol SR without compatibility issues.

Characteristics

Name	Method	Units	Aircol SR 32	Aircol SR 46	Aircol SR 68	Aircol SR 100
Density @ 15.6°C	ASTM D 4052	g/ml	0.83	0.84	0.84	0.84
Kinematic Viscosity @ 40°C	ASTM D 445	mm ² /s	32	46	68	100
Kinematic Viscosity @ 100°C	ASTM D 445	mm ² /s	6.1	7.8	10.7	14.0
Viscosity Index	ASTM D 2270	-				

Castrol Aircol SR Range

12 Mar 2012

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, North America Inc., 150 West Warrenville Road, 603 1E Naperville, IL 60563

Tel: (877) 641 1600 Fax: (877) 648 9801

www.castrol.com/industrial